

G3-1034/36/38 PTO POWERED (BUILD YOUR OWN) ORCHARD SPRAYER



Option



Option



Option



Standard Feature

Hydraulic Spray Valves

2-Point Turning Hitch

DK Turning Hitch

Adjustable Air Vanes

Davis & Davis Distributors
507 E. Dinuba Avenue • Reedley, Ca 93654
(Ph)559-638-6546 • (Fax)559-638-9262
Visit us: www.airofan.com • Contact us: info@airofan.com



G3-1034/36/38 1,000 GALLON PTO DRIVE SPRAYER

STANDARD FEATURES

- 1000 gal. 304 stainless steel tank
- 36 GPM / 600 PSI Comet® diaphragm pump
- Galvanized fan housing
- 34" dia., 8-blade axial flow steel fan (minimum 80 H.P. required)
- Composite nylon adjustable air vanes (2 nozzles per vane)
- Teejet® Stainless steel nozzles
- 2 speed gearbox with neutral
- Heavy duty PTO shaft, constant velocity joint
- Tank drive shaft w/ run down clutch
- Cable type remote control
- 16.5L x 16.1 Ribbed tires w/heavy duty hubs & adjustable spindles
- 1" Stainless steel mechanical agitation

OPTIONS

- Air-O-Fan 90° D.K. turning hitch, and 2-Point Turning hitch options
- Double or single lip heavy duty swivel hitch
- Multiple tire configurations
- 100 GPM / 145 PSI, Myers® 2-stage centrifugal pump
- 53 GPM / 600 PSI comet® pump (IDS 2200)
- 2" & 3" stainless steel fill connections
- Hydraulic and electric control valves
- Rear leaf guard
- 36" & 38" diameter, 8-blade axial flow steel fan (minimum 90 H.P. required)
- Tree sensing and flow monitoring systems

SPECIFICATION

LENGTH.....16', 7"
WIDTH.....101" (OUTSIDE OF TIRES)
HEIGHT.....71"-79" ADJUSTABLE
WEIGHT.....3,760 LBS.
AIR VELOCITY.....130 MPH (APPROX.)



Leaf Guard Option

2" Fill Front of Tank



Option



Swivel Hitch

Option



Option

Myers 2-Stage Centrifugal Pump

Visit our website: www.airofan.com