

G3-534/36 V-TOWER PTO POWERED VINEYARD SPRAYER



Indented Tank Option

Standard Feature



Adjustable Air Vanes



Option

Single & Double Lip Swivel Hitch



Option

Leaf Guard

Davis & Davis Distributors
507 E. Dinuba Avenue • Reedley, Ca 93654
(Ph)559-638-6546 • (Fax)559-638-9262
Visit us: www.airofan.com • Contact us: info@airofan.com



G3-534/36 VOLUTE TOWER

PTO DRIVE SPRAYER

STANDARD FEATURES

- 500 Gallon 304 stainless steel tank
- 26 GPM / 600 PSI Comet® diaphragm pump
- 34" diameter, 8-blade axial flow steel fan
- 2 speed gearbox with neutral
- Heavy duty constant velocity PTO shaft
- Tank drive shaft w/ rundown clutch
- 1" 304 stainless steel mechanical agitation
- Cable type remote control
- 304 stainless steel strainers
- 12.5Lx16.1 ribbed implement tires
- Heavy duty hubs and spindles
- Galvanized fan housing
- Stainless steel vineyard volute tower assembly
- Composite nylon adjustable air vanes w/specialty valves
- Teejet® stainless steel nozzles

OPTIONS

- 36 GPM / 600 PSI & 44 GPM / 600 PSI Comet® pump
- Dual hydraulic & electric spray control valves
- Stainless steel fill connections (2" & 3" couplers)
- Indented tank w/10.00x15" ribbed tires (60" wide)
- 2-Point, and DK turning hitches
- Ribbed implement & turf tire options
- Rear leaf guard
- 36" fan upgrade

SPECIFICATIONS

Length.....14'3"

Width.....78"

Height.....62" to 68"(top of tank)75"(tower top)

Weight.....2,780 lbs.

Air velocity...120 mph (approx.)

PTO Horse Power Requirements...65-95

Visit us: www.airofan.com

