

GB-36R 500 PTO POWERED ORCHARD SPRAYER



V-Tower Option



Option



Standard Feature



Standard Feature

2" Fill Front of Tank
W/Valve & Camlock

DK Turning Hitch Assembly

Adjustable Air Vanes

Davis & Davis Distributors
507 E. Dinuba Avenue • Reedley, Ca 93654
(Ph)559-638-6546 • (Fax)559-638-9262
Visit us: www.airofan.com • Contact us: info@airofan.com



GB-36R 500 "VOLUTE-TOWER" PTO DRIVE SPRAYER

STANDARD FEATURES

- 500 Gallon 304 stainless steel tank
- 36 GPM / 600 PSI Comet® diaphragm pump
- 36" diameter, 8-blade axial flow steel fan
- 2 speed gearbox with neutral
- Heavy duty PTO shaft
- Tank drive shaft w/ rundown clutch
- 1" 304 stainless steel mechanical agitation
- Cable type remote control
- 304 stainless steel strainers
- Teejet® ceramic nozzles
- 13.5Lx16.1 ANS field and turf tires
- Galvanized fan housing
- Heavy duty adjustable hubs and spindles
- Air-O-Fan built vineyard volute tower
- Composite nylon adjustable air vanes w/ specialty valves

Electric & Hydraulic Spray valve Options



OPTIONS

- 600 gallon 304 stainless steel tank
- 2-Point Turning Hitch
- Indented tank
- Multiple tire configurations
- 100 GPM / 145 PSI Myers® 2-stage centrifugal pump
- 53 GPM / 600 PSI Comet® Pump (Model IDS 2200)
- Hydraulic and electric control valves
- 2" and 3" Stainless steel fill connections
- Tower extension doors
- Micro-Trak® Flow monitoring systems



2-Point Turning Hitch Option



Spray Extension Door Option

SPECIFICATIONS

Length.....500 Gal. = 15' / 600 Gal. = 15'6"
 Width.....500 Gal. = 6'6" / 600 Gal. = 6'9"
 Height.....Tower top = 77" / 62" to 68" (adjustable)
 Weight.....500 Gal. = 2,910 lbs. / 600 Gal. = 2,960 lbs.
 Air velocity.....130 mph (approx.)



DK Turning Plate Set-Up

Visit our website: www.airofan.com